ViewSonic®

VA800 LCD Display

17.4" LCD with advanced SuperClearMVA™ technology.

The VA800 is the revolutionary 17.4" LCD display with incredible picture quality from ViewSonic — the award-winning leader in visual display technology. With SuperClearMVA technology for a superior 400:1 contrast ratio (max) and image clarity, you're assured of fast response time and rich, brilliant color. Couple this with dual inputs, a wide 160˚ viewing angle and the advanced ergonomic pivoting screen, and the ViewSonic VA800 LCD display sets a new standard for display excellence.

- **SuperClear MVA technology**
  SuperClearMVA technology combines SuperClear® screen technology and innovative Multidomain Vertical Alignment technology, delivering high contrast, brilliant color, improved viewing angles and superior clarity for moving images.
- **Full 17.4" viewable screen**
  The VA800 displays a full, flat 17.4" viewable area with crisp detail and fully saturated color.
- **1280x1024 true resolution**
  Displays a crisp, clear native resolution of 1280x1024 for easy viewing. Automatically scales lower resolutions to fill the screen.
- **3X speed-LCD display**
  ViewSonic's innovative 3X-LCD display utilizes an advanced liquid crystal panel technology to dramatically improves video response for superior picture clarity and perfect focus — even when viewing moving images.
- **Super-wide viewing angles**
  160˚ horizontally and vertically.
- **Dual analog inputs**
  Switch easily between two computer systems to share the display — the VA800 even auto-detects which system is on.
- **Weighs only 18.7 pounds**
- **Three-year limited warranty**

ViewSonic®
See the difference.

ViewSonic®

VA800 LCD Display

17" TFT LCD DISPLAY WITH SUPERCLEARMVA™ TECHNOLOGY

LCD	**Type**	MVA, TFT active matrix LCD (16.7 million colors)
	Display Area	13" (H) x 10.9" (V), 17.4" diagonal
	Contrast Ratio	400:1 (max)
	Viewing Angle	160˚ horizontal, 160˚ vertical
	Light Source	Long life, 50,000 hour (typ)
	Brightness	220 cd/m² (max)
	Panel Surface	Anti-glare coat
INPUT SIGNAL	**Video**	RGB Analog (75 ohms, 0.7 Vp-p auto detect) x 2
	Sync	H/V separated (TTL), composite sync, sync-on-green
	Frequency	f_h:30~82kHz; f_v:50~75Hz
COMPATIBILITY	**PC**	Non-interlaced VGA up to 1600x1200
	Mac*	Power Mac™ up to 1280x1024
CONNECTOR	**Analog RGB**	15-pin mini D-sub x 2
	Power	DC IN to head
POWER	**Voltage**	AC 81–264V (universal) via external DC converter brick
	Consumption	65W (max)
USER CONTROLS	**Physical**	1, Down Arrow, Up Arrow, 2, Power (soft)
	OnView®	Contrast, brightness, autosync, ViewMatch® color, H-size, H-position, V-position, fine tune, background, smoothing, ViewMeter®, input select, language, recall
VIDEO INPUT	**Bandwidth**	135MHz
OPERATING CONDITIONS	**Temperature**	32–104° F (0–40° C)
	Humidity	10–90% (non-condensation)
DIMENSIONS	**Physical**	460mm (W) x 460mm (H) x 240mm (D) 18.1" x 18.1" x 9.4"
WEIGHT	**Net**	8.5 kgs (18.7 lbs)
OTHER		DDC1 & DDC2B
REGULATIONS		UL, CSA, FCC-B, CB, CE, DOC-B, TUV/ERGO, TUV/GS, TCO'99, Energy 2000, VCCI, BSMI, NEMKO, SEMKO, DEMKO, FIMKO, PCBC, NOM, GOST-R + HYGIENIC, ARGENTINA, PSB, C-TICK, CCIB + CCEE
POWER MANAGEMENT		Meets ENERGY STAR®, VESA® DPMS and TCO'99 standards
WARRANTY		Three-year limited warranty on parts, labor and backlight.

• ViewSonic Wizard
This software provides user-friendly installation.

• PerfectPortrait™ software
The included software enables the user to display in both landscape or portrait modes for full page viewing.

PIVOT® ENABLED

• Advanced ergonomic design
Optimum ergonomic design with height, tilt, swivel, pivot and adjustments.

• PC and Mac®* compatible

• VESA wall mountable
Mounts on most walls with ViewSonic's optional wall mount kit (WM-U1).

• Kensington® lock ready
Protect your assets with this attachment point for an anti-theft cable.

• TCO'99 and Energy 2000 certified

ISO 9001 BSI REGISTERED FM 40187

ISO 14001 BSI REGISTERED EMS 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic®
See the difference.®

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789
Phone (800) 888-8583 or (909) 444-8888 • In Canada (866) 463-4775 • Fax (909) 839-7922 • SalesInfo@ViewSonic.com • ViewSonic.com

*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2003 ViewSonic Corporation. All rights reserved. [10305-04B-12/02_0M] VS-2102